

Specifications

Top quality materials • Smart design • Built to last

| MODEL | PART # | LENGTH (in/cm) | WIDTH (in/cm) | DRINKING HEIGHT (in/cm) | SHIPPING WEIGHT (lbs/kg) | HEAT (CF=Constant Flow) | CAPACITY (gal/liter) | MAXIMUM ANIMAL CAPACITY |
|-------------------------------|--------|------------------------------|---------------|-------------------------|--------------------------|------------------------------------|----------------------|-------------------------|
| WaterMaster | | | | | | | | |
| WM 1200 | 18053 | 144/366 | 24/61 | 24/61 | 250/113 | CF Opt/Opt Imm & Self Reg Heat Cbl | 60/227 | 500 beef, 250 dairy |
| WM 96 | 18007 | 96/244 | 33/84 | 22/56 | 200/91 | CF Std/Opt Imm & Self Reg Heat Cbl | 75/284 | 300 beef, 150 dairy |
| WM 90 | 16467 | 90/229 | 33/84 | 22/56 | 180/82 | CF Std/Opt Imm & Self Reg Heat Cbl | 30/114 | 300 beef, 150 dairy |
| WM 600 | 18171 | 72/183 | 24/61 | 24/61 | 140/64 | CF Opt/Opt Imm & Self Reg Heat Cbl | 28/106 | 250 beef, 125 dairy |
| WM 54 | 16542 | 54/137 | 33/84 | 22/56 | 125/57 | CF Std/Opt Imm & Self Reg Heat Cbl | 18/68 | 200 beef, 100 dairy |
| WaterMatic | | | | | | | | |
| 1000 | 18110 | 42/107 | 42/107 | 26/66 | 120/54 | Opt Imm & Self Reg Heat Cbl | 22/83 | 275 beef, 135 dairy |
| 300 | 18050 | 36/91 | 21.5/55 | 26/66 | 69/31 | Opt Imm & Self Reg Heat Cbl | 8.2/31 | 125 beef, 60 dairy |
| 150S | 18222 | 33.5/85 | 14/36 | 13/33 | 39/18 | Opt Imm & Self Reg Heat Cbl | 4.2/16 | 100 sheep, 100 goats |
| 150 | 18166 | 33.5/85 | 14/36 | 18/46 | 47/21 | Opt Imm & Self Reg Heat Cbl | 4.2/16 | 40 beef, 40 horses |
| 100 | 18165 | 24.5/62 | 14/36 | 18/46 | 36/16 | Opt Imm & Self Reg Heat Cbl | 2.8/11 | 20 beef, 20 horses |
| Thrifty King | | | | | | | | |
| CT6 | 16440 | 72.5/184 | 39/99 | 19/48 | 210/95 | Opt Imm & Self Reg Heat Cbl | 55/208 | 300 beef |
| CT4-2000 | 16430 | 42.8/109 | 35/89 | 19/48 | 152/69 | Opt Imm & Self Reg Heat Cbl | 45.5/172 | 200 beef |
| CT2-2000 | 16299 | 42.8/109 | 24/61 | 19/48 | 90/41 | Opt Imm & Self Reg Heat Cbl | 28/106 | 100 beef |
| CT1-2000 | 16271 | 28/71 | 20.3/51 | 19/48 | 53/24 | Opt Imm & Self Reg Heat Cbl | 11.2/42 | 30 beef |
| OmniFount | | | | | | | | |
| Omni 5 | 16533 | 40/102 | 23.5/60 | 26/66 | 88/40 | 548W (4.6A@120V) | 16/61 | 150 beef |
| Omni 3 | 18270 | 31.5/80 | 22/56 | 26/66 | 75/34 | 548W (4.6A@120V) | 10/38 | 100 beef, 50 dairy |
| Omni 2 | 16619 | 28.3/72 | 14.5/37 | 18/46 | 45/20 | 298W (2.5A@120V) | 2.2/8 | 40 horses, 40 beef |
| CattleMaster | | | | | | | | |
| CM 1440 | 18252 | 145.5/396.6 | 23.5/59.7 | 16/41 | 272/123 | 1298W (10.9A@120V)/CF | 60/227 | 475 beef, 240 dairy |
| CM 840 | 18235 | 86/218.4 | 23.5/59.7 | 16/41 | 130/64 | 1048W (8.8A@120V)/CF | 35/133 | 300 beef, 150 dairy |
| CM 480 | 18248 | 51/129.5 | 23.5/59.7 | 16/41 | 98/45 | 548W (4.6A@120V)/CF | 20/76 | 200 beef, 100 dairy |
| Cattle Fountain | | | | | | | | |
| 5 | 16745 | 38.4/98 | 20.1/51 | 26/66 | 101/46 | 548W (4.6A@120V)/Opt Gas | 16/61 | 150 beef, 75 dairy |
| 3 | 16743 | 29.6/75 | 18/46 | 26/66 | 82/37 | 548W (4.6A@120V)/Opt Gas | 10/38 | 100 beef, 50 dairy |
| Combination Fountain | | | | | | | | |
| 3 Combination | 16769 | 29.6/75 | 18/46 | 26/66 | 100/45 | 798W (6.7A@120V)/Opt Gas | 10/38 | 100 beef, 80 hogs |
| AC Series | | | | | | | | |
| 2AC | 18033 | 25.9/66 | 11.4/29 | 17.8/45 | 38/17 | 298W (2.5A@120V) | 2.2/8 | 40 beef, 80 calves |
| 1AC | 18034 | 17.6/45 | 11.4/29 | 17.8/45 | 28/13 | 298W (2.5A@120V) | 1.5/6 | 20 beef, 40 calves |
| 2AC Special | 18043 | 25.9/66 | 11.4/29 | 10.8/27 | 30/14 | 298W (2.5A@120V) | 2.2/8 | 40 beef, 80 calves |
| Commander Series | | | | | | | | |
| Comm. 2 | 16758 | 32.7/83 | 17/43 | 16/41 | 68/31 | 298W (2.5A@120V) | 6.5/25 | 60 beef |
| Comm. 1 | 16751 | 20.1/51 | 17/43 | 16/41 | 41/19 | 173W (1.4A@120V) | 3.5/13 | 30 beef |
| Stall Fount | | | | | | | | |
| Stall Fount 125 | 18082 | 14/36 | 13/33 | Adjustable | 31/14 | 173W (1.4A@120V) | 1.9/7 | single stall |
| Stall Fount | 16871 | 14/36 | 13/33 | Adjustable | 15/7 | NA | 1.9/7 | single stall |
| Shroud Set | 18092 | 19.4/49 each (2 sections) | 7/18 | Up to 4' | 16/7 | NA | NA | NA |
| Pork King | | | | | | | | |
| PK 4 | 16459 | 31.5/80 | 23.3/59 | 7/18 | 63/29 | 548W (4.6A@120V) | 3.5/13 | 160 hogs |
| PK 2-1 | 16458 | 23.2/59 | 23.3/59 | 7/18 | 50/23 | 298W (2.5A@120V) | 2/8 | 80 hogs |
| PK 2 | 16457 | 31.5/80 | 13/33 | 7/18 | 42/19 | 298W (2.5A@120V) | 2/8 | 80 hogs |
| PK 1 | 16456 | 23.2/59 | 13/33 | 7/18 | 30/14 | 298W (2.5A@120V) | 1.2/5 | 40 hogs |
| Thrifty King for Swine | | | | | | | | |
| HG 4 | 16260 | 31.3/80 | 31.3/80 | 8/20 | 70/32 | Opt Immersion | 5.2/20 | 160 hogs |
| HG 2 | 16259 | 31.3/80 | 20/51 | 8/20 | 50/23 | Opt Immersion | 2/8 | 80 hogs |



Poly products warranty: 5 years full, followed by 5 years prorated. **Steel products warranty:** 10 years, 100% on stainless troughs against manufacturing defects and corrosion; 1 year full and 9 years prorated on casing and cover. No competitors offer a warranty this strong.