



RAGING BULL

The UK-built “Raging Bull” Hydraulic



Above: optional boom/swing arm and weigh system.



Left: optional hydraulic headscoop. Right: hydraulic neck stretcher comes as standard.

Heavy-weight: 1.8 tonnes of robust quality. Galvanized. Hydraulic tail gate, squeeze mechanism, head gate and neck stretcher. Multiple gates and access areas all over the crush, making numerous tasks safer and easier, e.g. belly-trimming, caesarians, calf fostering and A.I. / P.D. work. Extra wide: to fit the very largest stock bulls, it squeezes from 33 inches internal width (the widest on the market) down to 10 inches. Double head gate (front and rear) for double T.B. testing. Rapid throughput: the head gate does not just catch the beast but actually pulls it into the squeeze crush; likewise the tail gate pushes the beast in. Built-in extra elbow/shoulder working room for A.I. technician. Pallet fork sleeves for safer moving. Hydraulic neck stretcher gives a stable part of the neck for vaccinations, T.B. testing, tagging, bolusing, de-horning, etc. In addition, when trimming bellies or fostering on calves, it stops the beast lurching backwards and forwards. Power pack and pressure system to run off single phase electric.

Optional extras include (photos overleaf):

- boom/swing arm on which to house controls
- hydraulic head scoop
- weigh systems
- hoof trimming attachments
- vet gates



Goosehill Beef Service GBS
Gbs.fi
+ 358 40 5390746